

# Crisafulli 2 and 2.5 Inch J-Series Vertical Pumps™



## VERTICAL ELECTRIC PUMPS

J - Series - Industrial Duty Standard Models

Sizes 2", and 2.5" Standard Options

**Description.** SRS Crisafulli™ J-Series Industrial Duty Vertical Pumps are direct driven centrifugal pumps, manufactured in standard 6 foot lengths from base to discharge (optional lengths available), complete with an A36 steel pump volute and impeller, drive shaft, one double roller thrust bearing, three or more ball bearings, bearing protection systems with extended lubrication lines, motor base plate, electric motor, NPT threaded discharge (standard), A36 steel pump mount plate included.

**Performance capabilities.** See below for performance capabilities.

Size, Description, Performance Industrial Duty Standard Model	SRSC Part Number	Est. weight pounds	HP	Solids Passing inches	Flow GPM	TDH Feet
2" Direct Drive, 1,150 RPM	VD029V-002-6	250	2	15/16	125	10
2" Direct Drive, 1,150 RPM	VD029V-003-6	275	3	15/16	140	20
2" Direct Drive, 1,150 RPM	VD029V-005-6	285	5	15/16	140	30
2" Direct Drive, 1,750 RPM	VD029V-005-4	285	5	15/16	200	20
2" Direct Drive, 1,750 RPM	VD029V-007-4	330	7.5	15/16	225	40
2" Direct Drive, 1,750 RPM	VD029V-010-4	360	10	15/16	240	60
2.5" Direct Drive, 1,150 RPM	VD259V-002-6	300	2	1.5	200	10
2.5" Direct Drive, 1,150 RPM	VD259V-003-6	310	3	1.5	175	20
2.5" Direct Drive, 1,150 RPM	VD259V-004-6	350	4	1.5	275	25
2.5" Direct Drive, 1,150 RPM	VD259V-005-6	360	5	1.5	275	30
2.5" Direct Drive, 1,750 RPM	VD259V-007-4	370	7.5	1.5	275	20
2.5" Direct Drive, 1,750 RPM	VD259V-010-4	400	10	1.5	300	40
2.5" Direct Drive, 1,750 RPM	VD259V-015-4	425	15	1.5	275	60
2.5" Direct Drive, 1,750 RPM	VD259V-020-4	450	20	1.5	300	80

NOTE: The final digit of the model number denotes the RPM of the electric motor: - 4 denotes 1,750 RPM; 6 denotes 1,150 RPM

### Standard Options & Accessories

Custom pump base plate(s)

Discharge adapters

Stainless steel wetted parts

Electrical control panels