

WP 15L Air Cooled Compressor



The 2-stage air-cooled compressors helped establish Sauer's reputation for high quality. After 75 years of production, these models are now in their third generation of development. These models are designed to have the following advantages:

- Direct drive (no belt maintenance)
- Light weight with small installation footprint
- Engineered for continuous operation in extreme environments
- Extended operation time between required maintenance intervals (2000 operating hours)

· SPECIFICATIONS · FLOW AND POWER

Stages/Cylinders	2/2
Operating Pressure Range	100 to 580 psi
Required Power @ 1150 RPM, 60 Hz	3.1 to 3.6 hp
Capacity F. A. D. @ 1150 RPM, 60 Hz	5.7 to 7.1 SCFM
Required Power @ 1770 RPM, 60 Hz	4.69 to 6.97 hp
Capacity F. A. D. @ 1770 RPM, 60 Hz	8 to 10 SCFM
Motor Rating @ 1170 RPM, 60 Hz	4 (3KW) hp
Motor Rating @ 1770 RPM, 60 Hz	7.5 (5.5KW) hp
Current @ 460 Volts @ 1170 RPM, 60 Hz	6.8 Amps
Current @ 460 Volts @ 1770 RPM, 60 Hz	9.3 Amps
Current @ 230 Volts @ 1170 RPM, 60 Hz	13.6 Amps
Current @ 230 Volts @ 1770 RPM, 60 Hz	18.6 Amps
Weight @ 1170 RPM, 60 Hz	305 Pound
Weight @ 1770 RPM, 60 Hz	300 Pound
Noise level @ 3 ft, 1170 RPM (60Hz)	82 dB(A)
Noise level @ 3 ft, 1770 RPM (60Hz)	86 dB(A)
Heat Dissipation @ 1170 RPM, 60 Hz	17,000 Btu/hr
Heat Dissipation @ 1770 RPM, 60 Hz	20,500 Btu/hr
Cooling Air Needed @ 1170 RPM, 60 Hz	410 CFM
Cooling Air Needed @ 1770 RPM, 60 Hz	590 CFM

Residual oil content at gas outlet (without filtration)	
Delta temperature (gas outlet vs. ambient) @ 1170 RPM, 60 Hz	16 °F
Delta temperature (gas outlet vs. ambient) @ 1770 RPM, 60 Hz	18 °F
Operational ambient temperature range	40-140 °F
Oil Sump Capacity	1.6 Quarts
Overall Dimensions (L x W x H)	34 X 24 X 25 Inch
Cooling Method	Air-Cooled
Drive Type	Direct Drive
Inlet Pressure	0 psi

FLOW AND POWER

Power @ 145 PSIG, 1170 RPM, 60 Hz	3.1 hp
Flow @ 145 PSIG, 1170 RPM, 60 Hz	7.1 SCFM
Power @ 145 PSIG, 1770 RPM, 60 Hz	4.7 hp
Flow @ 145 PSIG, 1770 RPM, 60 Hz	10.9 SCFM
Power @ 290 PSIG, 1170 RPM, 60 Hz	3.4 hp
Flow @ 290 PSIG, 1170 RPM, 60 Hz	6.9 SCFM
Power @ 290 PSIG, 1770 RPM, 60 Hz	5.0 hp
Flow @ 290 PSIG, 1770 RPM, 60 Hz	10.4 SCFM
Power @ 435 PSIG, 1170 RPM, 60 Hz	3.6 hp
Flow @ 435 PSIG, 1170 RPM, 60 Hz	6.6 SCFM
Power @ 435 PSIG, 1770 RPM, 60 Hz	5.5 hp
Flow @ 435 PSIG, 1770 RPM, 60 Hz	9.8 SCFM
Power @ 580 PSIG, 1170 RPM, 60 Hz	3.6 hp
Flow @ 580 PSIG, 1170 RPM, 60 Hz	5.8 SCFM
Power @ 580 PSIG, 1770 RPM, 60 Hz	7.0 hp
Flow @ 580 PSIG, 1770 RPM, 60 Hz	8.2 SCFM

WP 22L Air Cooled Compressor



The 2-stage air-cooled compressors helped establish Sauer's reputation for high quality. After 75 years of production, these models are now in their third generation of development. These models are designed to have the following advantages:

- Direct drive (no belt maintenance)
- Light weight with small installation footprint
- Engineered for continuous operation in extreme environments
- Extended operation time between required maintenance intervals (2000 operating hours)

· SPECIFICATIONS · FLOW AND POWER

Stages/Cylinders	2/2
Operating Pressure Range	100 to 580 psi
Required Power @ 1150 RPM, 60 Hz	4 to 4.7 hp
Capacity F. A. D. @ 1150 RPM, 60 Hz	8.24 to 9.18 SCFM
Required Power @ 1770 RPM, 60 Hz	6.3 to 7.6 hp
Capacity F. A. D. @ 1770 RPM, 60 Hz	12 to 14 SCFM
Motor Rating @ 1170 RPM, 60 Hz	5 (3.6KW) hp
Motor Rating @ 1770 RPM, 60 Hz	8.6 (6.4KW) hp
Current @ 460 Volts @ 1170 RPM, 60 Hz	8.1 Amps
Current @ 460 Volts @ 1770 RPM, 60 Hz	11.5 Amps
Current @ 230 Volts @ 1170 RPM, 60 Hz	16.2 Amps
Current @ 230 Volts @ 1770 RPM, 60 Hz	23 Amps
Weight @ 1170 RPM, 60 Hz	297 Pound
Weight @ 1770 RPM, 60 Hz	297 Pound
Noise level @ 3 ft, 1170 RPM (60Hz)	83 dB(A)
Noise level @ 3 ft, 1770 RPM (60Hz)	87 dB(A)
Heat Dissipation @ 1170 RPM, 60 Hz	17,000 Btu/hr
Heat Dissipation @ 1770 RPM, 60 Hz	27,000 Btu/hr
Cooling Air Needed @ 1170 RPM, 60 Hz	410 CFM
Cooling Air Needed @ 1770 RPM, 60 Hz	760 CFM

Residual oil content at gas outlet (without filtration)	
Delta temperature (gas outlet vs. ambient) @ 1170 RPM, 60 Hz	18 °F
Delta temperature (gas outlet vs. ambient) @ 1770 RPM, 60 Hz	25 °F
Operational ambient temperature range	40-140 °F
Oil Sump Capacity	1.6 Quarts
Overall Dimensions (L x W x H)	34 X 24 X 25 Inch
Cooling Method	Air Cooled
Drive Type	Direct Drive
Inlet Pressure	1 psi

FLOW AND POWER

Power @ 145 PSIG, 1170 RPM, 60 Hz	4.0 hp
Flow @ 145 PSIG, 1170 RPM, 60 Hz	9.2 SCFM
Power @ 145 PSIG, 1770 RPM, 60 Hz	6.3 hp
Flow @ 145 PSIG, 1770 RPM, 60 Hz	14.2 SCFM
Power @ 290 PSIG, 1170 RPM, 60 Hz	4.2 hp
Flow @ 290 PSIG, 1170 RPM, 60 Hz	8.8 SCFM
Power @ 290 PSIG, 1770 RPM, 60 Hz	6.4 hp
Flow @ 290 PSIG, 1770 RPM, 60 Hz	13.6 SCFM
Power @ 435 PSIG, 1170 RPM, 60 Hz	4.7 hp
Flow @ 435 PSIG, 1170 RPM, 60 Hz	8.6 SCFM
Power @ 435 PSIG, 1770 RPM, 60 Hz	7.2 hp
Flow @ 435 PSIG, 1770 RPM, 60 Hz	13.3 SCFM
Power @ 580 PSIG, 1170 RPM, 60 Hz	5.0 hp
Flow @ 580 PSIG, 1170 RPM, 60 Hz	8.2 SCFM
Power @ 580 PSIG, 1770 RPM, 60 Hz	7.6 hp
Flow @ 580 PSIG, 1770 RPM, 60 Hz	12.4 SCFM

WP 33L Air Cooled Compressor



The 2-stage air-cooled compressors helped establish Sauer's reputation for high quality. After 75 years of production, these models are now in their third generation of development. These models are designed to have the following advantages:

- Direct drive (no belt maintenance)
- Light weight with small installation footprint
- Engineered for continuous operation in extreme environments
- Extended operation time between required maintenance intervals (2000 operating hours)

· SPECIFICATIONS · FLOW AND POWER SPECIFICATIONS

Stages/Cylinders	2/2
Operating Pressure Range	100 to 580 psi
Required Power @ 1150 RPM, 60 Hz	5.9 to 7.2 hp
Capacity F. A. D. @ 1150 RPM, 60 Hz	11.2 to 12.7 SCFM
Required Power @ 1770 RPM, 60 Hz	8.9 to 10.9 hp
Capacity F. A. D. @ 1770 RPM, 60 Hz	18.7 to 19.3 SCFM
Motor Rating @ 1170 RPM, 60 Hz	6.4 (4.8 KW) hp
Motor Rating @ 1770 RPM, 60 Hz	11.6(8.6KW) hp
Current @ 460 Volts @ 1170 RPM, 60 Hz	10 Amps
Current @ 460 Volts @ 1770 RPM, 60 Hz	16.2 Amps
Current @ 230 Volts @ 1170 RPM, 60 Hz	20 Amps
Current @ 230 Volts @ 1770 RPM, 60 Hz	32.4 Amps
Weight @ 1170 RPM, 60 Hz	319 Pound
Weight @ 1770 RPM, 60 Hz	319 Pound
Noise level @ 3 ft, 1170 RPM (60Hz)	84 dB(A)
Noise level @ 3 ft, 1770 RPM (60Hz)	88 dB(A)
Heat Dissipation @ 1170 RPM, 60 Hz	20,000 Btu/hr
Heat Dissipation @ 1770 RPM, 60 Hz	34,000 Btu/hr
Cooling Air Needed @ 1170 RPM, 60 Hz	590 CFM
Cooling Air Needed @ 1770 RPM, 60 Hz	1,000 CFM

Residual oil content at gas outlet (without filtration)	
Delta temperature (gas outlet vs. ambient) @ 1170 RPM, 60 Hz	45 °F
Delta temperature (gas outlet vs. ambient) @ 1770 RPM, 60 Hz	72 °F
Operational ambient temperature range	40-140 °F
Oil Sump Capacity	1.6 Quarts
Overall Dimensions (L x W x H)	34 X 24 X 25 Inch
Cooling Method	Air Cooled
Drive Type	Direct Drive

FLOW AND POWER

Power @ 145 PSIG, 1170 RPM, 60 Hz	5.9 hp
Flow @ 145 PSIG, 1170 RPM, 60 Hz	12.6 SCFM
Power @ 145 PSIG, 1770 RPM, 60 Hz	9.0 hp
Flow @ 145 PSIG, 1770 RPM, 60 Hz	19.4 SCFM
Power @ 290 PSIG, 1170 RPM, 60 Hz	6.2 hp
Flow @ 290 PSIG, 1170 RPM, 60 Hz	12.2 SCFM
Power @ 290 PSIG, 1770 RPM, 60 Hz	9.4 hp
Flow @ 290 PSIG, 1770 RPM, 60 Hz	18.5 SCFM
Power @ 435 PSIG, 1170 RPM, 60 Hz	6.8 hp
Flow @ 435 PSIG, 1170 RPM, 60 Hz	11.9 SCFM
Power @ 435 PSIG, 1770 RPM, 60 Hz	10.5 hp
Flow @ 435 PSIG, 1770 RPM, 60 Hz	18.1 SCFM
Power @ 580 PSIG, 1170 RPM, 60 Hz	7.2 hp
Flow @ 580 PSIG, 1170 RPM, 60 Hz	11.2 SCFM
Power @ 580 PSIG, 1770 RPM, 60 Hz	11.0 hp
Flow @ 580 PSIG, 1770 RPM, 60 Hz	18.7 SCFM

WP 45L Air Cooled Compressor



The 2-stage air-cooled compressors helped establish Sauer's reputation for high quality. After 75 years of production, these models are now in their third generation of development. These models are designed to have the following advantages:

- Direct drive (no belt maintenance)
- Light weight with small installation footprint
- Engineered for continuous operation in extreme environments
- Extended operation time between required maintenance intervals (2000 operating hours)

SPECIFICATIONS · FLOW AND POWER

SPECIFICATIONS

Stages/Cylinders	2/2
Operating Pressure Range	100 to 580 psi
Required Power @ 1150 RPM, 60 Hz	11 to 13.4 hp
Capacity F. A. D. @ 1150 RPM, 60 Hz	20 to 23.2 SCFM
Required Power @ 1770 RPM, 60 Hz	13.2 to 16 hp
Capacity F. A. D. @ 1770 RPM, 60 Hz	31.4 to 35.7 SCFM
Motor Rating @ 1170 RPM, 60 Hz	10 hp
Motor Rating @ 1770 RPM, 60 Hz	15 hp
Current @ 460 Volts @ 1170 RPM, 60 Hz	13.4 Amps
Current @ 460 Volts @ 1770 RPM, 60 Hz	17.9 Amps
Current @ 230 Volts @ 1170 RPM, 60 Hz	26.8 Amps
Current @ 230 Volts @ 1770 RPM, 60 Hz	35.8 Amps
Weight @ 1170 RPM, 60 Hz	699.6 Pound
Weight @ 1770 RPM, 60 Hz	699.6 Pound
Noise level @ 3 ft, 1170 RPM (60Hz)	83 dB(A)
Noise level @ 3 ft, 1770 RPM (60Hz)	87 dB(A)
Heat Dissipation @ 1170 RPM, 60 Hz	34,000 Btu/hr
Heat Dissipation @ 1770 RPM, 60 Hz	51,000 Btu/hr
Cooling Air Needed @ 1170 RPM, 60 Hz	1,000 CFM

Cooling Air Needed @ 1770 RPM, 60 Hz	1,530 CFM
Residual oil content at gas outlet (without filtration)	
Delta temperature (gas outlet vs. ambient) @ 1170 RPM, 60 Hz	16 °F
Delta temperature (gas outlet vs. ambient) @ 1770 RPM, 60 Hz	22 °F
Operational ambient temperature range	40-130 °F
Oil Sump Capacity	5.5 Quarts
Overall Dimensions (L x W x H)	48 X 29 X 32 Inch
Cooling Method	Air- Cooled
Drive Type	Direct Drive

FLOW AND POWER

Power @ 145 PSIG, 1170 RPM, 60 Hz	8.7 hp
Flow @ 145 PSIG, 1170 RPM, 60 Hz	23.2 SCFM
Power @ 145 PSIG, 1770 RPM, 60 Hz	13.3 hp
Flow @ 145 PSIG, 1770 RPM, 60 Hz	35.7 SCFM
Power @ 290 PSIG, 1170 RPM, 60 Hz	9.7 hp
Flow @ 290 PSIG, 1170 RPM, 60 Hz	22.2 SCFM
Power @ 290 PSIG, 1770 RPM, 60 Hz	14.6 hp
Flow @ 290 PSIG, 1770 RPM, 60 Hz	34.3 SCFM
Power @ 435 PSIG, 1170 RPM, 60 Hz	10.2 hp
Flow @ 435 PSIG, 1170 RPM, 60 Hz	20.8 SCFM
Power @ 435 PSIG, 1770 RPM, 60 Hz	15.4 hp
Flow @ 435 PSIG, 1770 RPM, 60 Hz	33.2 SCFM
Power @ 580 PSIG, 1170 RPM, 60 Hz	10.7 hp
Flow @ 580 PSIG, 1170 RPM, 60 Hz	20.0 SCFM
Power @ 580 PSIG, 1770 RPM, 60 Hz	16.1 hp
Flow @ 580 PSIG, 1770 RPM, 60 Hz	31.5 SCFM

WP 65L Air Cooled Compressor



The 2-stage air-cooled compressors helped establish Sauer's reputation for high quality. After 75 years of production, these models are now in their third generation of development. These models are designed to have the following advantages:

- Direct drive (no belt maintenance)
- Light weight with small installation footprint
- Engineered for continuous operation in extreme environments
- Extended operation time between required maintenance intervals (2000 operating hours)

· SPECIFICATIONS · FLOW AND POWER

SPECIFICATIONS

Stages/Cylinders	2/2
Operating Pressure Range	100 to 580 psi
Required Power @ 1150 RPM, 60 Hz	14.6 to 17.8 hp
Capacity F. A. D. @ 1150 RPM, 60 Hz	26.8 to 30.4 SCFM
Required Power @ 1770 RPM, 60 Hz	17.6 to 21.5 hp
Capacity F. A. D. @ 1770 RPM, 60 Hz	41 to 47 SCFM
Motor Rating @ 1170 RPM, 60 Hz	15 hp
Motor Rating @ 1770 RPM, 60 Hz	20 hp
Current @ 460 Volts @ 1170 RPM, 60 Hz	17.3 Amps
Current @ 460 Volts @ 1770 RPM, 60 Hz	24.4 Amps
Current @ 230 Volts @ 1170 RPM, 60 Hz	34.6 Amps
Current @ 230 Volts @ 1770 RPM, 60 Hz	48.8 Amps
Weight @ 1170 RPM, 60 Hz	721.6 Pound
Weight @ 1770 RPM, 60 Hz	721.6 Pound
Noise level @ 3 ft, 1170 RPM (60Hz)	84 dB(A)
Noise level @ 3 ft, 1770 RPM (60Hz)	88 dB(A)
Heat Dissipation @ 1170 RPM, 60 Hz	51,000 Btu/hr
Heat Dissipation @ 1770 RPM, 60 Hz	68,000 Btu/hr
Cooling Air Needed @ 1170 RPM, 60 Hz	1,530 CFM

Cooling Air Needed @ 1770 RPM, 60 Hz	2,060 CFM
Residual oil content at gas outlet (without filtration)	
Delta temperature (gas outlet vs. ambient) @ 1170 RPM, 60 Hz	22 °F
Delta temperature (gas outlet vs. ambient) @ 1770 RPM, 60 Hz	31 °F
Operational ambient temperature range	40-130 °F
Oil Sump Capacity	5.5 Quarts
Overall Dimensions (L x W x H)	48 X 29 X 32 Inch
Cooling Method	Air Cooled
Drive Type	Direct Drive

FLOW AND POWER

Power @ 145 PSIG, 1170 RPM, 60 Hz	11.7 hp
Flow @ 145 PSIG, 1170 RPM, 60 Hz	30.4 SCFM
Power @ 145 PSIG, 1770 RPM, 60 Hz	17.7 hp
Flow @ 145 PSIG, 1770 RPM, 60 Hz	46.9 SCFM
Power @ 290 PSIG, 1170 RPM, 60 Hz	13.0 hp
Flow @ 290 PSIG, 1170 RPM, 60 Hz	29.2 SCFM
Power @ 290 PSIG, 1770 RPM, 60 Hz	19.6 hp
Flow @ 290 PSIG, 1770 RPM, 60 Hz	44.2 SCFM
Power @ 435 PSIG, 1170 RPM, 60 Hz	13.7 hp
Flow @ 435 PSIG, 1170 RPM, 60 Hz	28.4 SCFM
Power @ 435 PSIG, 1770 RPM, 60 Hz	20.6 hp
Flow @ 435 PSIG, 1770 RPM, 60 Hz	42.7 SCFM
Power @ 580 PSIG, 1170 RPM, 60 Hz	14.2 hp
Flow @ 580 PSIG, 1170 RPM, 60 Hz	26.8 SCFM
Power @ 580 PSIG, 1770 RPM, 60 Hz	21.4 hp
Flow @ 580 PSIG, 1770 RPM, 60 Hz	40.9 SCFM

WP 146L Air Cooled Compressor



The 2-stage air-cooled compressors helped establish Sauer's reputation for high quality. After 75 years of production, these models are now in their third generation of development. These models are designed to have the following advantages:

- Direct drive (no belt maintenance)
- Light weight with small installation footprint
- Engineered for continuous operation in extreme environments
- Extended operation time between required maintenance intervals (2000 operating hours)

· SPECIFICATIONS · FLOW AND POWER

SPECIFICATIONS

Stages/Cylinders	2/2
Operating Pressure Range	87 to 145 psi
Required Power @ 1150 RPM, 60 Hz	22 to 23.5 hp
Capacity F. A. D. @ 1150 RPM, 60 Hz	62 to 65 SCFM
Required Power @ 1770 RPM, 60 Hz	32 to 35 hp
Capacity F. A. D. @ 1770 RPM, 60 Hz	88 to 92 SCFM
Motor Rating @ 1170 RPM, 60 Hz	25 hp
Motor Rating @ 1770 RPM, 60 Hz	40 hp
Current @ 460 Volts @ 1170 RPM, 60 Hz	29.8 Amps
Current @ 460 Volts @ 1770 RPM, 60 Hz	47.6 Amps
Current @ 230 Volts @ 1170 RPM, 60 Hz	59.6 Amps
Current @ 230 Volts @ 1770 RPM, 60 Hz	95.2 Amps
Weight @ 1170 RPM, 60 Hz	1434.4 Pound
Weight @ 1770 RPM, 60 Hz	1434.4 Pound
Noise level @ 3 ft, 1170 RPM (60Hz)	86 dB(A)
Noise level @ 3 ft, 1770 RPM (60Hz)	89 dB(A)
Heat Dissipation @ 1170 RPM, 60 Hz	68,000 Btu/hr
Heat Dissipation @ 1770 RPM, 60 Hz	99,000 Btu/hr
Cooling Air Needed @ 1170 RPM, 60 Hz	2,060 CFM

Cooling Air Needed @ 1770 RPM, 60 Hz	3,060 CFM
Residual oil content at gas outlet (without filtration)	
Delta temperature (gas outlet vs. ambient) @ 1170 RPM, 60 Hz	18 °F
Delta temperature (gas outlet vs. ambient) @ 1770 RPM, 60 Hz	23 °F
Operational ambient temperature range	40-130 °F
Oil Sump Capacity	13.7 Quarts
Overall Dimensions (L x W x H)	56 X 34 X 35 Inch
Cooling Method	Air Cooled
Drive Type	Direct Drive

FLOW AND POWER

Power @ 100 PSIG, 1170 RPM, 60 Hz	22.0 hp
Flow @ 100 PSIG, 1170 RPM, 60 Hz	64.8 SCFM
Power @ 100PSIG, 1770 RPM, 60 Hz	32.0 hp
Flow @ 100 PSIG, 1770 RPM, 60 Hz	92.3 SCFM
Power @ 115PSIG, 1170 RPM, 60 Hz	22.8 hp
Flow @ 115 PSIG, 1170 RPM, 60 Hz	62.9 SCFM
Power @ 115 PSIG, 1770 RPM, 60 Hz	33.5 hp
Flow @ 115 PSIG, 1770 RPM, 60 Hz	89.4 SCFM
Power @ 145 PSIG, 1170 RPM, 60 Hz	23.5 hp
Flow @ 145 PSIG, 1170 RPM, 60 Hz	62.4 SCFM
Power @ 145 PSIG, 1770 RPM, 60 Hz	34.9 hp
Flow @ 145 PSIG, 1770 RPM, 60 Hz	88.2 SCFM

WP 226L Air Cooled Compressor



The 2-stage air-cooled compressors helped establish Sauer's reputation for high quality. After 75 years of production, these models are now in their third generation of development. These models are designed to have the following advantages:

- Direct drive (no belt maintenance)
- Light weight with small installation footprint
- Engineered for continuous operation in extreme environments
- Extended operation time between required maintenance intervals (2000 operating hours)

· SPECIFICATIONS · FLOW AND POWER

SPECIFICATIONS

Stages/Cylinders	2/2
Operating Pressure Range	87 to 145 psi
Required Power @ 1150 RPM, 60 Hz	30.4 to 33 hp
Capacity F. A. D. @ 1150 RPM, 60 Hz	112.1 to 113.7 SCFM
Required Power @ 1770 RPM, 60 Hz	51.4 to 55.7 hp
Capacity F. A. D. @ 1770 RPM, 60 Hz	152.7 to 154.4 SCFM
Motor Rating @ 1170 RPM, 60 Hz	40 hp
Motor Rating @ 1770 RPM, 60 Hz	60 hp
Current @ 460 Volts @ 1170 RPM, 60 Hz	47.1 Amps
Current @ 460 Volts @ 1770 RPM, 60 Hz	67 Amps
Current @ 230 Volts @ 1170 RPM, 60 Hz	94.2 Amps
Current @ 230 Volts @ 1770 RPM, 60 Hz	134 Amps
Weight @ 1170 RPM, 60 Hz	1584 Pound
Weight @ 1770 RPM, 60 Hz	1584 Pound
Noise level @ 3 ft, 1170 RPM (60Hz)	87 dB(A)
Noise level @ 3 ft, 1770 RPM (60Hz)	90 dB(A)
Heat Dissipation @ 1170 RPM, 60 Hz	133,000 Btu/hr
Heat Dissipation @ 1770 RPM, 60 Hz	198,000 Btu/hr
Cooling Air Needed @ 1170 RPM, 60 Hz	4,120 CFM

Cooling Air Needed @ 1770 RPM, 60 Hz	6,120 CFM
Residual oil content at gas outlet (without filtration)	
Delta temperature (gas outlet vs. ambient) @ 1170 RPM, 60 Hz	20 °F
Delta temperature (gas outlet vs. ambient) @ 1770 RPM, 60 Hz	25 °F
Operational ambient temperature range	40-130 °F
Oil Sump Capacity	22.7 Quarts
Overall Dimensions (L x W x H)	68 X 40 X 40 Inch
Cooling Method	Air- Cooled
Drive Type	Direct Drive

FLOW AND POWER

Power @ 100 PSIG, 1170 RPM, 60 Hz	30.4 hp
Flow @ 100 PSIG, 1170 RPM, 60 Hz	113.8 SCFM
Power @ 100PSIG, 1770 RPM, 60 Hz	51.5 hp
Flow @ 100 PSIG, 1770 RPM, 60 Hz	154.4 SCFM
Power @ 115PSIG, 1170 RPM, 60 Hz	31.1 hp
Flow @ 115 PSIG, 1170 RPM, 60 Hz	112.8 SCFM
Power @ 115 PSIG, 1770 RPM, 60 Hz	52.5 hp
Flow @ 115 PSIG, 1770 RPM, 60 Hz	153.5 SCFM
Power @ 145 PSIG, 1170 RPM, 60 Hz	33.0 hp
Flow @ 145 PSIG, 1170 RPM, 60 Hz	112.1 SCFM
Power @ 145 PSIG, 1770 RPM, 60 Hz	55.8 hp
Flow @ 145 PSIG, 1770 RPM, 60 Hz	152.7 SCFM