

# Crisafulli 2 and 2.5 Inch S-Series Vertical Pumps™



## VERTICAL ELECTRIC PUMPS

S - Series - Standard Duty Standard Models

Sizes 2", and 2.5" - Standard Options

**Description.** SRS Crisafulli™ Standard Duty "S" Series Vertical Pumps are manufactured with an abrasion resistant, heat treated alloy steel pump volute and impeller (Brinell 400 hardness). The pump drive shaft and bearings are totally enclosed in an oil filled ventilated enclosure with tandem mechanical shaft seals, and flanged discharge. A36 steel pump mount plate included.

**Performance capabilities.** See below for performance capabilities.

Size, Description, Performance Standard Duty Standard Models	SRSC Part Number	Est. weight pounds	HP	Solids Passing inches	Flow GPM	TDH Feet
2" Direct Drive	VD022V-001-4	250	1	.5	70	15
2" Direct Drive	VD022V-002-4	260	2	.5	80	20
2" Direct Drive	VD022V-003-4	280	3	.5	90	25
2" Direct Drive	VD029V-005-4	290	5	.5	110	30
2" Direct Drive	VD22HPV-005-2	295	5	.5	100	40
2" Direct Drive	VD2HPV-010-2	340	10	.5	120	60
2" Direct Drive	VD2HPV-015-2	350	15	.5	150	100
2.5" Direct Drive	VD252V-003-4	300	3	.5	200	15
2.5" Direct Drive	VD252V-005-4	310	5	.5	250	25
2.5" Direct Drive	VD252HPS-015-2	475	15	.5	300	40
2.5" Direct Drive	VD252HPS-020-2	500	20	.5	325	60
2.5" Direct Drive	VD252HPS-025-2	625	25	.5	350	80

NOTE: The final digit of the model number denotes the RPM of the electric motor: - 4 denotes 1,750 RPM; 6 denotes 1,150 RPM

## Standard Options & Accessories

Custom pump base plate(s)

Discharge adapters

Stainless steel wetted parts

Electrical control panels