

# Crisafulli 3 Inch S-Series Vertical Pumps™



## VERTICAL ELECTRIC PUMPS

S - Series - Standard Duty Standard Models

Sizes 3" - Standard Options

**Description.** SRS Crisafulli™ Standard Duty "S" Series Vertical Pumps are manufactured with an abrasion resistant, heat treated alloy steel pump volute and impeller (Brinell 400 hardness). The pump drive shaft and bearings are totally enclosed in an oil filled ventilated enclosure with tandem mechanical shaft seals, and flanged discharge. A36 steel pump mount plate included.

**Performance capabilities.** See below for performance capabilities.

Size, Description, Performance Standard Duty Standard Models	SRSC Part Number	Est. weight pounds	HP	Solids Passing inches	Flow GPM	TDH Feet
3" Direct Drive	VD032S-005-4	350	5	1.75	200	20
3" Direct Drive	VD032S-007-4	400	7.5	1.75	275	25
3" Direct Drive	VD032S-010-4	410	10	1.75	325	30
3" Direct Drive	VD032S-015-4	515	15	1.75	375	35
3" Direct Drive	VD032S-020-4	540	20	1.75	375	35

NOTE: The final digit of the model number denotes the RPM of the electric motor: - 4 denotes 1,750 RPM; 6 denotes 1,150 RPM

### Standard Options & Accessories

- Custom pump base plate(s)
- Discharge adapters
- Stainless steel wetted parts
- Electrical control panels