

Crisafulli 6 Inch J-Series Vertical Pumps™



VERTICAL ELECTRIC PUMPS

J - Series - Industrial Duty - Standard Models

Sizes 6" - Standard Options

Description. SRS Crisafulli™ J-Series Industrial Duty Vertical Pumps are direct driven centrifugal pumps, manufactured in standard 6 foot lengths from base to discharge (optional lengths available), complete with an A36 steel pump volute and impeller, drive shaft, one double roller thrust bearing, three or more ball bearings, bearing protection systems with extended lubrication lines, motor base plate, electric motor, NPT threaded discharge (standard), A36 steel pump mount plate included. Standard length is 20'.

Performance capabilities. See below for performance capabilities.

Size, Description, Performance Industrial Duty Standard Model	SRSC Part Number	Est. weight pounds	HP	Solids Passing inches	Flow GPM	TDH Feet
6" Direct Drive, 1,150 RPM	VD049V-060-6	1,150	60	3	1,800	60
6" Direct Drive, 1,150 RPM	VD049V-075-6	1,300	75	3	1,800	70
6" Direct Drive, 1,150 RPM	VD049V-075-6	1,300	75	3	1,800	80
6" Direct Drive, 1,150 RPM	VD049V-100-6	1,700	100	3	1,700	90
6" Direct Drive, 1,150 RPM	VD049V-100-6	1,700	100	3	1,600	100
6" Direct Drive, 1,750 RPM	VD049V-100-4	1,700	100	3	1,300	120
6" Direct Drive, 1,750 RPM	VD949V-125-4	1,900	125	3	1,500	140
6" Direct Drive, 1,750 RPM	VD049V-150-4	2,200	150	3	1,600	160
6" Direct Drive, 1,750 RPM	VD049V-175-4	2,500	175	3	1,750	180
6" Direct Drive, 1,750 RPM	VD049V-200-4	2,800	200	3	1,900	200

NOTE: The final digit of the model number denotes the RPM of the electric motor: - 4 denotes 1,750 RPM; 6 denotes 1,150 RPM

Standard Options & Accessories

Custom pump base plate(s)

Discharge adapters

Stainless steel wetted parts

Electrical control panels