




BERKELEY® 6TSP SERIES SUBMERSIBLE PUMPS

The 6TSP series pumps feature abrasion and corrosion resistant materials for maximum performance and longevity under the toughest operating conditions.

Components are 100% lead-free, and meet all U.S. federal guidelines for safe drinking water.



- 1 Discharge - 304 stainless steel, investment cast, 3" FNPT**
Features 6 extra wide wrench flats for a secure grip when tightening to the drop pipe.
- 2 Standard Check valve - 304 stainless steel**
The poppet-style check valve helps protect the pump against backflow. The check valve can be easily removed if not required.
- 3 Shaft and bearing assembly - 416 stainless steel**
A ceramic upper bearing guide combined with a cutless rubber bearing protects the shaft from premature wear.
- 4 Impellers and diffusers - glass-filled Noryl®**
Smooth and efficient performance, and superior sand handling.
- 5 Wear rings - 304 stainless steel and polyurethane**
Minimizes re-circulation for increased pump performance and longevity.
- 6 Pump sleeve - 304 stainless steel**
Provides superior corrosion resistance when the pump is installed in harsh environments.
- 7 Lead guard - 304 stainless steel**
Easy installation, and protects the motor leads across the full length of the pump.
- 8 Suction bracket - 304 stainless steel, investment cast**
Machined for both 4" and 6" motor registers. Bolt kits included for either motor size where appropriate.
- 9 Suction screen - 304 stainless steel**
Form fitted, provides corrosion resistance, and prevents particulates larger than 0.10" from entering the pump.
- 10 Motor Coupling - 316 stainless steel**
Designed to effectively divert debris away from the spline engagement area to maximize durability.


NORYL® IS A REGISTERED TRADEMARK OF GE.
BERKELEY® IS A REGISTERED TRADEMARK OF PENTAIR LTD.

BERKELEY® 6TSP SERIES SUBMERSIBLE PUMPS

Materials of Construction

Part Name	Material	Reference
Discharge, check valve, lead guard, suction bracket, suction screen	304 stainless steel	ASTM A743 CF-8
Motor coupling	316 stainless steel	AISI 316 stainless steel
Shaft	416 stainless steel	AISI 416 stainless steel
Wear rings	304 stainless steel polyurethane	ASTM A743 CF-8
Impellers, diffusers	Noryl®	
Upper guide bearing	ceramic	

BEC2 ELECTRONIC CATALOG
 Powerful pump selection and application software.
 Visit www.berkeleypumps.com
 and click the BEC2 icon to get started.



50 GPM / 75 GPM / 100 GPM



293 WRIGHT STREET, DELAVAN, WI 53115 WWW.BERKELEYPUMPS.COM
 PH: 888-237-5353 ORDERS FAX: 800-321-8793

BERKELEY® and Pentair are registered trademarks of Pentair Ltd. NORYL® is a registered trademark of GE.
 Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice.