

Complete Line of Drill Modules

Versatile. Rugged. Reliable.

Our innovative product line now includes a modern & efficient drill module that instantly matches the footprint of a Sullair® module. Featuring a Sullair® single-stage rotary screw air compressor. Vanair offers drill packages up to 1500 cfm at 500 psi in single and two stage configurations and can be completely tailored to meet your drilling customer's needs.



Specifications

Model	Delivery* cfm (m ³ /m)	Pressure* psig (bar)	RPM***	Power*** BHP (kW)	Weight with Receiver lbs (Kg)	Dimensions LxWxH In. (mm)
Shaft or Hydraulic Drive (Less Motor)						
225/100 Module	225 (6.4)	100 (7.6)	2300	56 (42)	980 (445)	71 x 30 x 38 (1803 x 762 x 965)
310/200 Module	310 (8.9)	200 (13.8)	2500	110 (82)	1225 (556)	73 x 30 x 49 (1854 x 762 x 1244)
Single-Stage Low-Pressure - Direct Shaft Driven						
375/100 Module	375 (10.6)	100 (7.6)	2450	89 (66)	1400 (636)	36 x 36 x 34 (914 x 914 x 1372)
435/200 Module	405 (11.5)	200 (13.8)	1900	141 (105)	1400 (636)	36 x 36 x 34 (914 x 914 x 1372)
500/100 Module	475 (13.5)	100 (7.6)	2000	117 (87)	1400 (636)	36 x 36 x 34 (914 x 914 x 1372)
500/200 Module	500 (14.2)	200 (13.8)	2000	167 (125)	1400 (636)	36 x 36 x 34 (914 x 914 x 1372)
750/100 Module	750 (21.2)	100 (7.6)	1800	186 (139)	2425 (1100)	48 x 43 x 62 (1219 x 1092 x 1575)
900/100 Module	900 (25.5)	100 (7.6)	1800	216 (161)	2425 (1100)	48 x 43 x 62 (1219 x 1092 x 1575)
1050/100 Module	1050 (29.8)	100 (7.6)	1800	250 (187)	3045 (1381)	54 x 43 x 69 (1219 x 1092 x 1753)
Single-Stage Low-Pressure - Direct Shaft Driven						
750/250 Module	750 (21.2)	250 (17)	1900	254 (189)	4910 (2227)	75 x 53 x 62 (1905 x 1346 x 1575)
750/300 Module	750 (21.2)	300 (21)	1900	271 (202)	4910 (2227)	58 x 42 x 43 (1473 x 1067 x 1092)
750/350 Module	750 (21.2)	350 (24)	1900	288 (215)	4910 (2227)	58 x 42 x 43 (1473 x 1067 x 1092)
750/350 Open Frame	750 (21.2)	350 (24)	1900	288 (215)	5800 (2630)	80 x 76 x 58 (2032 x 1930 x 1473)
900/250 Module	900 (25.5)	250 (17)	1850	327 (244)	5325 (2415)	75 x 63 x 52 (1905 x 1600 x 1321)
900/300 Module	900 (25.5)	300 (21)	1850	345 (257)	5325 (2415)	75 x 63 x 52 (1905 x 1600 x 1321)
900/350 Module	900 (25.5)	350 (24)	1850	363 (271)	5325 (2415)	75 x 63 x 52 (1905 x 1600 x 1321)

Specifications

900/350 Open Frame	900 (25.5)	350 (24)	1850	363 (271)	5800 (2630)	80 x 76 x 58 (2032 x 1930 x 1473)
900/500 Module	900 (25.5)	500 (34)	1850	415 (310)	5325 (2415)	75 x 63 x 52 (1905 x 1600 x 1321)
1150/250 Module	1150 (32.6)	250 (17)	2000	399 (298)	5970 (2708)	77 x 53 x 62 (1956 x 1346 x 1575)
1150/300 Module	1150 (32.6)	300 (21)	2000	441 (329)	5970 (2708)	77 x 53 x 62 (1956 x 1346 x 1575)
1150/350 Module	1150 (32.6)	350 (24)	2000	441 (329)	5970 (2708)	77 x 53 x 62 (1956 x 1346 x 1575)
1150/350 Open Frame	1150 (32.6)	350 (24)	2000	441 (329)	6350 (2880)	94 x 76 x 68 (2388 x 1930 x 1727)

* For other deliveries and pressure, please consult factory.

** For other available speeds, please consult factory.

*** The horsepower figures represent nominal BHP needed at the input shaft and include requirements for a cooler fan, which is built into modular systems. For ratings on other configurations, please consult factory. An increase to 500 PSI on the two stage high pressure units 1150 CFM and above requires additional externally mounted cooler. See Engineering for added cost of cooler and air end.

Product improvement is a continuing goal. Design and specifications are subject to change without notice or obligations.