

MR 5-30 Mechanical Fuel Meter



Choose the **NEW MR 5-30 mechanical fuel meter** when you need to measure petroleum fuels. This aluminum meter is perfect for use with gasoline, diesel fuel and kerosene. Designed for high volume pumps up to 30 GPM.

Watch the MR 5-30 video on YouTube.

Fitting	Mechanical Connection	Flow Range	Accuracy	Operating Temperature	Display	Reads	Pressure Rating	Model	Warranty
NPT	¾ in. Inlet ¾ in. Outlet	5 to 30 GPM 19 to 114 LPM	±2 % of reading	-20 to 125 °F -29 to 52 °C	Mechanical Batch: 4; Total: 8 Digits	Gallons	3.4 bar 50 PSI	MR 5-30-G6N	2 Years
NPT	¾ in. Inlet ¾ in. Outlet	5 to 30 GPM 19 to 114 LPM	±2 % of reading	-20 to 125 °F -29 to 52 °C	Mechanical Batch: 4; Total: 8 Digits	Litres	3.4 bar 50 PSI	MR 5-30-L6N	2 Years
BSPP	¾ in. Inlet ¾ in. Outlet	5 to 30 GPM 19 to 114 LPM	±2 % of reading	-20 to 125 °F -29 to 52 °C	Mechanical Batch: 4; Total: 8 Digits	Litres	3.4 bar 50 PSI	MR 5-30-L6B	2 Years
NPT	1 in. Inlet 1 in. Outlet	5 to 30 GPM 19 to 114 LPM	±2 % of reading	-20 to 125 °F -29 to 52 °C	Mechanical Batch: 4; Total: 8 Digits	Gallons	3.4 bar 50 PSI	MR 5-30-G8N	2 Years
NPT	1 in. Inlet 1 in. Outlet	5 to 30 GPM 19 to 114 LPM	±2 % of reading	-20 to 125 °F -29 to 52 °C	Mechanical Batch: 4; Total: 8 Digits	Litres	3.4 bar 50 PSI	MR 5-30-L8N	2 Years
BSPP	1 in. Inlet 1 in. Outlet	5 to 30 GPM 19 to 114 LPM	±2 % of reading	-20 to 125 °F -29 to 52 °C	Mechanical Batch: 4; Total: 8 Digits	Litres	3.4 bar 50 PSI	MR 5-30-L8B	2 Years
NPT	1 ½ in. Inlet 1 ½ in. Outlet	5 to 30 GPM 19 to 114 LPM	±2 % of reading	-20 to 125 °F -29 to 52 °C	Mechanical Batch: 4; Total: 8 Digits	Gallons	3.4 bar 50 PSI	MR 5-30-G12N	2 Years
NPT	1 ½ in. Inlet 1 ½ in. Outlet	5 to 30 GPM 19 to 114 LPM	±2 % of reading	-20 to 125 °F -29 to 52 °C	Mechanical Batch: 4; Total: 8 Digits	Litres	3.4 bar 50 PSI	MR 5-30-L12N	2 Years
BSPP	1 ½ in. Inlet 1 ½ in. Outlet	5 to 30 GPM 19 to 114 LPM	±2 % of reading	-20 to 125 °F -29 to 52 °C	Mechanical Batch: 4; Total: 8 Digits	Litres	3.4 bar 50 PSI	MR 5-30-L12B	2 Years
NPT	1 ½ in. Inlet 1 ½ in. Outlet	5 to 30 GPM 19 to 114 LPM	±2 % of reading	-20 to 125 °F -29 to 52 °C	Mechanical Batch: 4; Total: 8 Digits	Gallons or Litres	3.4 bar 50 PSI	MR 5-30N	2 Years
NPT	1 ½ in. Inlet 1 ½ in. Outlet	5 to 30 GPM 19 to 114 LPM	±2 % of reading	-20 to 125 °F -29 to 52 °C	Mechanical Batch: 4; Total: 8 Digits	Gallons or Litres	3.4 bar 50 PSI	MR 5-30N	2 Years