

Crisafulli Submersible Electric Pumps™ S-Series 1150 RPM



Performance capabilities range from 500 to 600 GPM depending on the size selected. 3 Models. Total Dynamic Heads (TDH) range from 10 feet to 30 feet, depending on the pump size and electric motor selected. See below for GPM and TDH for each model listed. Solids passing capability 2-1/4 inches for all models.

Description. SRS Crisafulli Submersible Electric Pumps are American made, direct driven, centrifugal pumps. The pumps are manufactured with an ASTM A36 mild carbon steel (BN 150 or BN 400 hardness) pump volute and impeller, dual carbon/ceramic shaft seals, UL listed, totally enclosed, air filled, non-ventilated, explosion-proof electric motor, (Class 1, Groups C & D, hazardous locations), moisture detection probes, thermal overload protection, 25 feet of power and control cable (additional length available) and gray epoxy paint. All pumps with motors larger than 5 horsepower are 460 volt, 3 phase only. (Consult factory for motor sizes smaller than 5 HP, and for other special voltages.)

Pump Size Inches	Horse Power HP	Flow-GPM	TDH-Feet	Solids Passing Capability Inches	SRSC Part Number	Impeller Size Inches
4	7.5	500	10	2.25	SE042R-005-6	8
4	10	575	20	2.25	SE042R-007-6	9
4	15	600	30	2.25	SE042R-010-6	10

Standard Options

- Case & Impeller from AR Steel BN 400 Hardness
- Case & Impeller from 316 Stainless Steel
- Electrical Control Panels
- Mercury Float Switches
- Tungsten Carbide Seals
- Additional Cable