

# Mini Fire-Ball® 225, 50:1

## Air-Powered Grease Pumps and Packages

### Features and Benefits

- Non-corrosive air motor design for long life
- Double-acting pump ensures smooth fluid flow
- Robust grease inlet cage withstands the most abusive handling

### Typical Applications

- Medium pressure, low to medium volume grease dispense
- Automotive dealerships
- Heavy-duty dealerships
- Fast lube and service centers
- Fleet service facilities
- Lube trucks
- Mining
- In-plant

### Typical Fluids Handled

- Grease up to NLGI #2


### Technical Specifications

Continuous-Duty Flow Rate .....	0.32 lb/min (0.15 kg/min)
Maximum Fluid Pressure .....	8400 psi (578 bar)
Air Motor Effective Diameter .....	2.25 in (57.2 mm)
Operating Range .....	40-140 psi (3-10 bar)
Approximate Air Use .....	7.3 scfm @ 0.41 lb/min. (.18 kg/min) @ 100 psi @ 80 cpm
Wetted Materials .....	Steel, Urethane, Aluminum, Buna-N, Brass, Ethylene, Delrin®
Air Inlet Port Size .....	3/8 in npt(f)
Material Inlet .....	Slotted
Material Outlet .....	1/4 in npt(f)
Line Length ‡ .....	Up to 100 ft (30.5 m)
Dispense Points .....	1
Annual Usage .....	Up to 10,000 lb (4,535 kg)

### Ordering Information

Mini Fire-Ball 225 50:1 Pumps	
246909	35 lb (16 kg) Grease Pump - 50:1
246780	120 lb (55 kg) Grease Pump - 50:1
246781	400 lb (180 kg) Grease Pump - 50:1

### Pump Performance



‡ Consult your local authorized Graco representative for line or pipe sizing

# Fire-Ball® 300, 15:1

## Air-Powered Grease Pumps and Packages

### Features and Benefits

- Non-corrosive air motor design for long life
- Double-acting pump ensures smooth fluid flow
- Robust grease inlet cage withstands the most abusive handling

### Typical Applications

- Medium pressure, low to medium volume grease dispense
- Automotive dealerships
- Heavy-duty dealerships
- Fast lube and service centers
- Fleet service facilities
- Lube trucks
- Mining
- In-plant

### Typical Fluids Handled

- Grease up to NLGI #2


### Technical Specifications

Continuous-Duty Flow Rate .....	0.7 gpm
Maximum Fluid Pressure .....	2700 psi (186 bar)
Air Motor Effective Diameter .....	3 in (7.6 cm)
Operating Range .....	40-180 psi (2.8-12.5 bar)
Approximate Air Use .....	17 cfm@ 100 psi (7 bar)
Wetted Materials .....	CS, AL, Leather, PTFE, Rubber
Air Inlet Port Size .....	3/8 in npt(f)
Material Inlet .....	1 in npt(f) Straight Inlet
Material Outlet .....	1/4 in npt(f)
Line Length ‡ .....	Up to 250 ft (76.2 m)
Dispense Points .....	1 to 2
Annual Usage .....	Up to 10,000 lb (4,535 kg)

### Ordering Information

Fire-Ball 300 15:1 Pumps	
206405	35 lb (16 kg) Grease Pump - 15:1
206699	120 lb (55 kg) Grease Pump - 15:1
206700	400 lb (180 kg) Grease Pump - 15:1

### Pump Performance



‡ Consult your local authorized Graco representative for line or pipe sizing

# Fire-Ball® 300, 50:1

## Air-Powered Grease Pumps and Packages

### Features and Benefits

- Non-corrosive air motor design for long life
- Double-acting pump ensures smooth fluid flow
- Robust grease inlet cage withstands the most abusive handling

### Typical Applications

- Medium pressure, low to medium volume grease dispense
- Automotive dealerships
- Heavy-duty dealerships
- Fast lube and service centers
- Fleet service facilities
- Lube trucks
- Mining
- In-plant

### Typical Fluids Handled

- Grease up to NLGI #2


### Technical Specifications

Continuous-Duty Flow Rate .....	1.19 lb/min. (.54 kg/min.)
Maximum Fluid Pressure .....	8400 psi (580 bar)
Air Motor Effective Diameter .....	3 in (76.2 cm)
Operating Range .....	30-140 psi (3.0-9.7 bar)
Approximate Air Use .....	22.8 cfm @100 psi (7 bar)
Wetted Materials .....	CS, Delrin®, Buna-N, Polyurethane
Air Inlet Port Size .....	3/8 in npt(f)
Material Inlet .....	Slotted
Material Outlet .....	1/4 in npt(f)
Line Length‡ .....	Up to 250 ft (76.2 m)
Dispense Points .....	1 to 2
Annual Usage .....	Up to 10,000 lb (4,535 kg)

### Ordering Information

Fire-Ball 300 15:1 Pumps	
239877	35 lb or 70 lb (16 kg or 32 kg) Grease Pump - 50:1
239887	120 lb (55 kg) Grease Pump - 50:1
239888	400 lb (180 kg) Grease Pump - 50:1

### Pump Performance



‡ Consult your local authorized Graco representative for line or pipe sizing

# Fire-Ball® 425, 10:1

## Air-Powered Grease Pumps and Packages

### Features and Benefits

- Non-corrosive air motor design for long life
- Double-acting pump ensures smooth fluid flow
- Robust grease inlet cage withstands the most abusive handling

### Typical Applications

- Medium pressure, low to medium volume grease dispense
- Automotive dealerships
- Heavy-duty dealerships
- Fast lube and service centers
- Fleet service facilities
- Lube trucks
- Mining
- In-plant

### Typical Fluids Handled

- Grease up to NLGI #2


### Technical Specifications

Continuous-Duty Flow Rate .....	3.5 gpm
Maximum Fluid Pressure .....	1800 psi (124 bar)
Air Motor Effective Diameter .....	4.25 in (10.8 cm)
Operating Range .....	40-180 psi (2.8-12.5 bar)
Approximate Air Use .....	13 cfm @100 psi (7 bar)
Wetted Materials .....	Steel, Bass, Aluminum, Leather, Buna-N
Air Inlet Port Size .....	1/2 in npt(f)
Material Inlet .....	Slotted
Material Outlet .....	1 in npt(f)
Line Length ‡ .....	Up to 500 ft (152.4 m)
Dispense Points .....	4 or more
Annual Usage .....	20,000 lb or more (9,072 kg)

### Ordering Information

Fire-Ball 425 10:1 Pumps	
965124	Stubby mount Fire-Ball 425, 10:1 pump only

### Pump Performance



‡ Consult your local authorized Graco representative for line or pipe sizing

# Fire-Ball® 425, 50:1

## Air-Powered Grease Pumps and Packages

### Features and Benefits

- Non-corrosive air motor design for long life
- Double-acting pump ensures smooth fluid flow
- Robust grease inlet cage withstands the most abusive handling

### Typical Applications

- Medium pressure, low to medium volume grease dispense
- Automotive dealerships
- Heavy-duty dealerships
- Fast lube and service centers
- Fleet service facilities
- Lube trucks
- Mining
- In-plant

### Typical Fluids Handled

- Grease up to NLGI #2


### Technical Specifications

Continuous-Duty Flow Rate .....	3.35 lb/min (1.5 kg/min.)
Maximum Fluid Pressure .....	7500 psi (517 bar)
Air Motor Effective Diameter .....	4.25 in (10.8 cm)
Operating Range .....	40-150 psi (2.8-10.4 bar)
Approximate Air Use .....	19 cfm @70 psi (4.8 bar)
Wetted Materials .....	CS, Leather
Air Inlet Port Size .....	1/2 in npt(f)
Material Inlet .....	Slotted
Material Outlet .....	3/8 in npt(f)
Line Length ‡ .....	Up to 250 ft (76.2 m)
Dispense Points .....	4 or more
Annual Usage .....	20,000 lb or more (9,072 kg)

### Ordering Information

Fire-Ball 425 50:1 Pumps	
205394	120 lb (55 kg) Grease Pump - 50:1
205395	400 lb (180 kg) Grease Pump - 50:1

### Pump Performance



Air Powered Grease Pumps and Packages

‡ Consult your local authorized Graco representative for line or pipe sizing

# Fire-Ball® 425, 75:1

## Air-Powered Grease Pumps and Packages

Air Powered Grease Pumps and Packages

### Features and Benefits

- Non-corrosive air motor design for long life
- Double-acting pump ensures smooth fluid flow
- Robust grease inlet cage withstands the most abusive handling

### Typical Applications

- Medium pressure, low to medium volume grease dispense
- Automotive dealerships
- Heavy-duty dealerships
- Fast lube and service centers
- Fleet service facilities
- Lube trucks
- Mining
- In-plant

### Typical Fluids Handled

- Grease up to NLGI #2


### Technical Specifications

Continuous-Duty Flow Rate .....	1.95 lb/min (0.88 kg/min)
Maximum Fluid Pressure .....	7500 psi (517 bar)
Air Motor Effective Diameter .....	4.25 in (10.8 cm)
Operating Range .....	40-100 psi (2.8-7 bar)
Approximate Air Use .....	26 cfm @100 psi (7 bar)
Wetted Materials .....	CS, Leather
Air Inlet Port Size .....	1/2 in npt(f)
Material Inlet .....	Slotted
Material Outlet .....	3/8 in npt(f)
Line Length ‡ .....	Up to 500 ft (152.5 m)
Dispense Points .....	4 or more
Annual Usage .....	20,000 lb or more (9,072 kg)

### Ordering Information

Fire-Ball 425 75:1 Pumps	
239729	120 lb (55 kg) Grease Pump - 75:1
239730	400 lb (180 kg) Grease Pump - 75:1
239731	35/70 lb (16/32 kg) Grease Pump - 75:1


### Pump Performance



‡ Consult your local authorized Graco representative for line or pipe sizing

# Fire-Ball® Grease Pump Packages

## Air-Powered Grease Pumps and Packages



### Mini Fire-Ball® 225, 50:1 Grease Pumps and Packages

	Portable Pail Dispenser	Stationary Pail Dispenser	Cart-Mounted Pail Dispenser	Stationary Supply Package	Portable Package w/ Caster Base	Portable Package w/ 2-Wheel Cart	Stationary Supply Package
Container Size	35 lb (16 kg) pail	35 lb (16 kg) pails or 70 lb (32 kg) bulk		120 lb (55 kg)			400 lb (180 kg)
Package No.	246910 +	246911 +	246913 +	246914 +	246915 +	246916 +	246917 +
Pump Only.	246909			246780			246781
Container	—	204134		—	—	—	—
Follower Plate	220653	*	*	220654			223845
Dispense Kit	236058			222072	236058		222072
Fluid Hose	12 ft x 1/4 in (3.7 m x 6.4 mm)			6 ft x 1/4 in (1.8 m x 6.4 mm)	12 ft x 1/4 in (3.7 m x 6.4 mm)		6 ft x 1/4 in (1.8 m x 6.4 mm)
Air Hose	222059	204574	204574	6 ft x 3/8 in (1.8 m x 9.5 mm)	—	—	6 ft x 3/8 in (1.8 m x 9.5 mm)
Cover	222059	204574			—		200326
Cart	—	—	203650	—	203622	203650	—
Manual	309967						

+ Order 3/8 in (9.5 mm) air regulator (109075) separately \* Order follower plate 220653 separately for 35 lb (16 kg) pails or 220654 for 70 lb (32 kg) bulk

### Fire-Ball® 300, 15:1 Grease Pumps and Packages

	Stationary Pail Dispenser	Stationary Drum Dispenser	Cover-Mounted Drum Dispenser
Container Size lb (kg)	35 lb (16 kg)	120 lb (55 kg)	400 lb (180 kg)
Package No.	222078	220170	220171
Pump Only	206405	206699	206700
Dispense Kit	222080	222081	222081
Fluid Hose	15 ft x 3/8 in (4.6 m x 9.5 mm)	25 ft x 3/8 in (7.6 m x 9.5 mm)	25 ft x 3/8 in (7.6 m x 9.5 mm)
Drum Cover	222058	204574	200326
Instruction Manual	307882		

# Fire-Ball® Grease Pump Packages

## Air-Powered Grease Pumps and Packages

### Fire-Ball® 300, 50:1 35-70 lb (16-32 kg) Grease Pumps and Packages

	Portable Pail Dispenser	Stationary Pail Dispenser	Cart-Mounted Pail Dispenser	Cart-Mounted Pail Topper
Container Size	35 lb (16 kg)	35 lb or 70 lb (16 kg or 32 kg)	35 lb or 70 lb (16 kg or 32 kg)	35 lb (16 kg)
Package No.	222069 *	225827 *	225773 *	226012 *
Metered Package**	245694	—	245695	—
Pump No.	239877			
Dispense Kit	222070			
Fluid Hose	12 ft x 1/4 in (3.7 m x 6.4 mm)			
Follower Plate	220653	†	†	—
Cover	222059	204574		—
Holster	—	203976		
Container	—	204134	204134	—
Cart	—	—	203650	
Elevator	—	—	—	203664
Inductor Plate	—	—	—	204351
Instruction Manual	307878			

\* Use 3/8 in (9.5 mm) air regulator 109075; must be ordered separately \*\* Metered grease package includes 233807 Accu-Shot instead of 242056 Pro-Shot † Order follower plate 220653 for 35 lb (16 kg) containers, and follower plate 220654 for 70 lb (32 kg) containers; must be ordered separately



### Fire-Ball® 300, 50:1 Packages For 120 lb (55 kg) Containers

	Portable with Caster Base	Portable with Two-Wheel Cart	Portable with Heavy-Duty Cart	Stationary Supply	Stationary Supply Topper-Inductor
Container Size lb (kg)	120 (55)	120 (55)	120 (55)	120 (55)	120 (55)
Package Number	225006 *	225026 *	222245 *	225014 *	222073 *
Metered Package	—	245696 **	—	—	—
Pump Only	239887	239887	239887	239887	239887
Dispense Kits	222070	222070	222383	222072	-
Fluid Hose	12 ft x 1/4 in (3.7 m x 6.4 mm)	—	25 ft x 1/4 in (7.6 m x 6.4 mm)	6 ft x 1/4 in (1.8 m x 6.4 mm)	6 ft x 1/4 in (1.8 m x 6.4 mm)
Air Hose	—	—	—	6 ft x 3/8 in (1.8 m x 9.5 mm)	6 ft x 3/8 in (1.8 m x 9.5 mm)
Follower Plate	220654	220654	220654	220654	—
Cover	204574	204574	222060	204574	—
Holster	203976	203976	—	—	—
Caster Base	203622	—	—	—	—
Cart	—	203650	222243	—	—
Elevator	—	—	—	—	204121
Pump Support	—	—	—	—	222074†
Hold Down Kit	—	—	222061	—	—
Instruction Manual	307878	307878	307878	307880	306523

\* Use 3/8 in (9.5 mm) air regulator 109075; must be ordered separately \*\* Metered grease package includes 233807 Accu-Shot instead of 242056 Pro-Shot † Pump support assembly includes dust cover, base, inductor plate and 6 ft (1.8 m) fluid & air hose



# Fire-Ball® Grease Pump Packages

## Air-Powered Grease Pumps and Packages

### Fire-Ball® 300, 50:1 Packages for 400 lb (180 kg) Containers

	Stationary	Topper-Inductor
Container Size lb (kg)	400 (180)	400 (180)
<b>Package Number</b>	<b>225016*</b>	<b>226013*</b>
Pump Only	239888	239888
Hose & Fitting Kit	222072	204467
Fluid Hose	6 ft (1.8 m) x 1/4 in (6.4 mm)	6 ft (1.8 m) x 1/4 in (6.4 mm)
Air Hose	6 ft (1.8 m) x 3/8 in (9.5 mm)	6 ft (1.8 m) x 3/8 in (9.5 mm)
Follower Plate	223845	—
Cover	200326	—
Carriage	—	204461
Elevator	—	204385
Inductor Plate	—	204353
Base	—	205339
Instruction Manual	307880	306556

\* Use 3/8 in (9.5 mm) air regulator 109075; must be ordered separately



400 lb. Stationary Supply Package



120 lb. Stationary Supply with Topper-Inductor



Stationary Supply Package



400 lb. Stationary Supply with Topper-Inductor

### Fire-Ball® 425, 10:1 Packages

#### 10:1 Pump for Closed Head Drum for 400 lb (180 kg)

965129	Fire-Ball 425, 10:1 pump complete with bung adapter. For open head drum, remove bung adapter and mount to 200326, 400 lb (180 kg) drum cover. Ideal for transferring grease from 400 lb (180 kg) drum or side pocket of tote tank. Can be modified for stubby horizontal mount on tote tanks. For more information contact Lubrication Equipment Technical Assistance
<b>Fire-Ball 425, 10:1 Pump Only</b>	
205394	Fire-Ball 425, 10:1 pump only, fits 120 lb. Open Drum
205395	Fire-Ball 425, 10:1 pump only, fits 400 lb. Open Drum
965124	Fire-Ball 425, 10:1 pump only, Stubby Universal Mount


### Fire-Ball® 425, 50:1; Bulldog® 3:1 Packages for 120-400 lb (56-180 kg) Containers

Description	Stationary Supply	Stationary Supply	Stationary Supply Topper-Inductor	Ram	Bulldog 3:1 (Sinkers)
Container Size lb (kg)	120 (55)	400 (180)	400 (180)	400 (180)	400 (180)
<b>Package Number</b>	<b>223108*</b>	<b>225781*</b>	<b>226018*</b>	<b>244905</b>	<b>244848</b>
Pump Only	205394	205395	205395	205395	205148
Air Hose Kit	222076	222076	205102	222076	208610
Fluid Hose	6 ft x 3/8 in (1.8 m x 9.5 mm)				
Air Hose	6 ft x 1/2 in (1.8 m x 12.7 mm)				
Cover	204574	200326	—	—	—
Follower Plate	223344	223846	—	—	—
Carriage	—	—	204461	—	—
Elevator	—	—	204385	—	—
Inductor Plate	—	—	205699	—	222404
Base	—	—	205339	—	—
Ram	—	—	—	—	—
Air Regulator	—	—	—	244844	207651
Adapter Plate	—	—	—	162225	—
Adapter Kit	—	—	—	224266	—
Manual	307880	307880	306556	309345	309345

\* Use 1/2 in (12.7 mm) air regulator 104266 and gauge 100960; must be ordered separately For Fire-Ball 425, 50:1 Lube Truck Packages, see the Specialty Pump Section

# Fire-Ball® Grease Pump Packages

## Air-Powered Grease Pumps and Packages



### Fire-Ball® 425, 75:1 Packages for 35-400 lb (16-180 kg) Containers

Description	Cover-Mount	Cover-Mount	Inductor	Ram	Pail Length	Bung or Cover
Container Size lb (kg)	120 (55)	400 (180)	400 (180)	400 (180)	35/70 lb (16/32 kg)	400 (180)
<b>Package Number</b>	<b>244635*</b>	<b>244636*</b>	<b>244637*</b>	<b>244906</b>	—	—
Pump Only	239729	239730	239730	239730	239731	239730
Hose and Fitting Kit	222076	222076	205102	222076	—	—
Drum Cover	204574	200326	—	—	204574	—
Follower Plate	223344	223846	—	—	**	—
Carriage	—	—	204461	—	—	—
Elevator	—	—	204385	—	—	—
Base	—	—	205339	—	—	—
Inductor	—	—	205699	—	—	—
Ram	—	—	—	—	—	—
Air Regulator	—	—	—	244844	—	—
Adapter Plate	—	—	—	162225	—	—
Adapter Kit	—	—	—	224266	—	—
Manual	307880	307880	306556	09345	—	—


\* Use 1/2 in (12.7 mm) air regulator (104266) and gauge (100960); must be ordered separately \*\* 35 lb: 220653/ 70 lb: 223344 • For Lube Truck Packages, see the Specialty Pumps and Packages Solution Section

### RAM Assemblies

Description	Fire-Ball 300, 50:1	Fire-Ball 425, 75:1	Fire-Ball 425, 50:1	Fire-Ball 425, 10:1	Bull Dog, 3:1**
<b>System Package</b>	<b>*</b>	<b>244906</b>	<b>244905</b>	<b>*</b>	<b>244641</b>
Bare Pump	239888	239730	205395	965129	205148
Ram	257435	—	—	—	—
Pump Mount Kit	247336	247337	247337	247337	—
Adapter Kit	224267	224266	224266	not needed	—
Air Regulator and Gauge	203716	244844	244844	207468	207651
Ram Plate Seal Kit	247335	247335	247335	247335	224829
Air Hose 3/4 in x 6 ft	—	—	—	—	208610


\*Order individual components \*\*Drum clamp when required 206537

### Drum Systems




#### Ram-Mount

- Force feed high volume pumps
- Extreme viscous grease
- Reduce waste
- Clean and convenient method of drum change



#### Inductor-Mount

- Reduce waste
- Clean and convenient method of drum change



#### Cover-Mount with Follower Plate

- Economical

# Fire-Ball® Grease Pump Accessories

## Air-Powered Grease Pumps and Packages

Dispense, Hose and Fitting Kits	
<b>Rated to 4,000-5,000 psi (345 bar) for Portable Fire-Ball 300, 50:1 or Mini Fire-Ball 225, 50:1 Pumps</b>	
222080	For Fire-Ball 300, 15:1. Includes: 15 ft (4.6 m) of 4,000 psi, 3/8 in (9.5 mm) fluid hose (109165), grease dispense valve (242056), Z-Swivel (202577), 3/8 in (9.5 mm) closed nipple (156849), quick-disconnect nipple (169971), quick-disconnect air coupler (110198) and 3/8 in (9.5 mm) air regulator (110234)
222081	For Fire-Ball 300, 15:1. Includes: 25 ft (7.6 m) of 4,000 psi, 3/8 in (9.5 mm) fluid hose (109167), grease dispense valve (242056), Z-Swivel (202577), 3/8 in (9.5 mm) closed nipple (156849), quick-disconnect nipple (169971), quick-disconnect air coupler (110198) and 3/8 in (9.5 mm) air regulator (110234)
236058	For Mini Fire-Ball 225, 50:1. Includes: 12 ft (3.6 m) fluid hose (109151), air coupler (208536), air nipple (169971), grease dispense valve (242056) and Z-Swivel (202577)
222070	For Fire-Ball 300, 50:1. Includes: 12 ft (3.6 m) fluid hose (109151), air coupler (208536), air nipple (169971), grease dispense valve (242056) and Z-Swivel (202577). Instruction manual 307878
222383	For Portable Units Powered by the Mini Fire-Ball 225, 50:1 or Fire-Ball 300, 50:1 Pumps. Includes dispense kit: grease dispense valve (242056), 25 ft (7.6 m) fluid hose (109154), air coupler (208536), air nipple (169971) and Z-Swivel (202577). Instruction manual 307878
Hose and Fitting Kits	
<b>Rated to 5000 psi (345 bar) for Stationary Drum-Mounted Fire-Ball 300, 50:1 Pumps</b>	
222072	Hose and Fittings Kit. Includes: 6 ft (1.8 m) air hose (203320) with swivel elbow (155494) and 6 ft (1.8 m) fluid hose (109150) with swivel elbow (155541). Instruction manual 307880
<b>Rated to 4000 psi (276 bar) for Stationary Drum-Mounted Fire-Ball 425, 50:1 Pumps</b>	
222076	Hose and Fittings Kit. Includes: 6 ft (1.8 m) air hose (205418) with swivel elbow (155470) and 6 ft (1.8 m) fluid hose (109163) with swivel elbow (155494). Instruction manual 307880
Bung Adapters	
239965	For Fire-Ball 425, 50:1 and 75:1 Pumps, 1.65 in ID
239966	For Fire-Ball 300, 15:1 and 50:1 Pumps
Lincoln-to-Graco Adapter Kit	
241246	For Fire-Ball 300, 50:1 when replacing a Series 20 Lincoln
Flange Mounting Accessories for Fire-Ball Pumps	
948393	Flange adapter (male) Fire-Ball 300
948392	Flange adapter (male) Fire-Ball 425
512874	Coupler (female)
Follower Plates	
220653	For 35 lb (16 kg) pails with Mini Fire-Ball 225, 50:1, Fire-Ball 300, 15:1 and 50:1 pumps
220654	For 70 and 120 lb (32/55 kg) drum, Mini Fire-Ball 225, 50:1, Fire-Ball 300, 15:1 and 50:1 pumps
223344	For 120 lb (55 kg) drums with Fire-Ball 425, 50:1 and 75:1 pumps
223700	For 120 lb (55 kg) drums with Dyna-Star 5:1 pumps
223845	For 400 lb (180 kg) drum, Mini Fire-Ball 225, 50:1, Fire-Ball 300, 15:1 and 50:1 pumps, 1.19 in ID
204130	Follower plate same as 223845, but without flexible wiper
223846	For 400 lb (180 kg) drums with Fire-Ball 425, 50:1 and 75:1 pumps, 1-13/32 in ID
205337	Follower plate same as 223846, but without flexible wiper
223701	For 400 lb (180 kg) drums with Dyna-Star 5:1 and Fire-Ball 425, 10:1 pumps, 2.1 in ID
Drum Covers	
200326	Cover for open-head 400 lb (180 kg) drums. Use with any Mini Fire-Ball 225-50:1, Fire-Ball 300-15:1 and 50:1, Fire-Ball 425-10:1 or Dyna-Star 5:1 pump. Use adapter 160754 for bung mounted pumps
204574	Cover for open-head 120 lb (55 kg) or 70 lb (32 kg) drums. Mounts Mini Fire-Ball 225, Fire-Ball grease pumps or Dyna-Star 5:1 pump. Use adapter 160754 for bung mounted pumps
222059	Cover for 35 lb (16 kg) pails. Mounts Mini Fire-Ball 225, 50:1 and Fire-Ball 300, 50:1 pumps using friction-style clutch lock. Allows use of 70 lb (32 kg) length pump with 35 lb (16 kg) pail
160754	Bung-adapter plate. Mounts to standard 400 lb (180 kg) or 120 lb (55 kg) drum cover and converts mounting to standard 2 npt bung opening. Allows use of bung-mounted pumps with drum covers



220653



204574



200326



222059



160754

# Fire-Ball® Grease Pump Accessories

## Air-Powered Grease Pumps and Packages

Air Powered Grease Pumps and Packages

Portable Bases	
205054	Band Dolly for 35 lb (16 kg) pails
204144	Band Dolly Base for 70 lb (32 kg) or 120 lb (55 kg) drums
203622	Caster Base for 35 lb (16 kg), 70 lb (32 kg) or 120 lb (55 kg) drums
Carts	
203650	For 35 lb (16 kg), 70 lb (32 kg) and 120 lb (55 kg) drums. Drums fit onto recess on formed base. Rim clamps secure drum onto cart. Use with pail clamp 159952 when using cart with 35 lb (16 kg) pails
222243	For 120 lb (55 kg) drums with pneumatic wheels for rough terrain
111470	Heavy-duty drum truck for 400 lb (180 kg) drums secures drum onto roll-around base
Drum Elevators	
241663	Air-Powered Elevator to speed drum changes. Maximum raised height: 39.5 in (100.33 cm). Includes: Cover Support (207562), Drum Elevator, (204385), Air Control Kit (207561)
Air Shut-Off Valves, Bleed-type, rated to 250 psi (17.4 bar)	
110223	1/4 in (6.4 mm)
110224	3/8 in (9.5 mm)
110225	1/2 in (12.7 mm)
110226	3/4 in (19.1 mm)
High-Pressure Grease Shut-Off Valves	
202869	5000 psi (345 bar) high-pressure needle valve, 1/2 npt(f) ported valve for drop-line isolation

