

Super Duty Vane Pumps



These are the pumps of choice for heavy construction, large farming and fleet operations. The 115-volt **M-3130** provides the highest flow rate of any GPI transfer pump. The 3/4 horsepower motor runs efficient and cool, extending pump life. The unique strainer and poppet design allows easy access and easy maintenance.

- Available with either manual or automatic nozzle.
- Comes with 12 feet of 1 inch UL grounded hose.
- Pump and Motor are UL Listed to U.S. and Canadian standards.
- Order the M-3295 for 230-volt models.

| Model | Design Type | Voltage | Reads | Mechanical Connection | Fitting | Flowrate | Nozzle | Motor Protection | Warranty |
|-----------|-------------|---------------------|-------------------|---|---------|---|-----------|--------------------------------------|----------|
| M-3130-ML | Vane | 115 or 230 Volts AC | Gallons Litres | 1 ¼ in. Inlet 1 in. Outlet | N/A | Up to 30 GPM Up to 114 LPM | Manual | Internal temperature-limiting device | 2 Years |
| M-3130-AD | Vane | 115 or 230 Volts AC | Gallons Litres | 1 ¼ in. Inlet 1 in. Outlet | N/A | Up to 30 GPM Up to 114 LPM | Automatic | Internal temperature-limiting device | 2 Years |
| M-3130-PO | Vane | 115 or 230 Volts AC | Gallons Litres | 1 ¼ in. Inlet 1 in. Outlet | N/A | Up to 30 GPM Up to 114 LPM | Pump Only | Internal temperature-limiting device | 2 Years |
| M-3295-ML | Vane | 230 Volts AC | Gallons Litres | 1 ¼ in. Inlet 1 in. Outlet 2 in. Bung | BSPP | At 50 Hz: up to 95 LPM At 60 Hz: up to 113.5 LPM | Manual | Internal temperature-limiting device | 2 Years |
| M-3295-AL | Vane | 230 Volts AC | Gallons Litres | 1 ¼ in. Inlet 1 in. Outlet 2 in. Bung | BSPP | At 50 Hz: up to 95 LPM At 60 Hz: up to 113.5 LPM | Automatic | Internal temperature-limiting device | 2 Years |
| M-3295-PO | Vane | 230 Volts AC | Gallons Litres | 1 ¼ in. Inlet 1 in. Outlet 2 in. Bung | BSPP | At 50 Hz: up to 95 LPM At 60 Hz: up to 113.5 LPM | Pump Only | Internal temperature-limiting device | 2 Years |